

1. Cover Prosidding



Conference Record
No. #57641

2023 International Conference on Computer Science, Information Technology and Engineering (ICCoSITE) | 979-8-3503-2095-4/23/\$31.00 ©2023 IEEE | DOI: 10.1109/ICCoSITE57641.2023.10127843

CONFERENCE

The 2023

ICCoSITE

International Conference on Computer Science, Information Technology & Engineering
Jakarta - Indonesia, 16 February 2023

**Digital Transformation Strategy
in Facing the VUCA & TUNA Era**

biic.binainsani.ac.id/ICCoSITE.html

2. Informasi dewan redaksi/editor/steering committee dan panitia pelaksana

The Committees

STEERING COMMITTEE

Prof. Ir. Gamantyo Hendranto, M.Eng., Ph.D. (IEEE Indonesia Section)
Dr.-Ing. Wahyudi Hasbi, S.Si., M.Kom. (National Research & Innovation Agency (BRIN), Indonesia)
Assoc. Prof. Dr. Indra Muis, S.S., M.M. (Universitas Bina Insani, Indonesia)
Shalahuddin, S.Pd., M.M. (Universitas Bina Insani, Indonesia)
Rita Wahyuni Arifin, S.Kom., M.Kom. (Universitas Bina Insani, Indonesia)
Kristiana Widiawati, S.Pd., M.M., CMA. (Universitas Bina Insani, Indonesia)

ORGANIZING COMMITTEE

General Chair

Ahmad Chusyairi (Universitas Bina Insani, Indonesia)

Treasurer

Lucia Ari Diyani (Universitas Bina Insani, Indonesia)

Secretary

Dwi Ismiyana Putri (Universitas Bina Insani, Indonesia)

Program Chair

Adrianus Trigunadi Santoso (Universitas Bina Insani, Indonesia)

Chita Oktapriana (Universitas Bina Insani, Indonesia)

Publication Chair

Dade Nurdiniah (Universitas Bina Insani, Indonesia)

Rully Pramudita (Universitas Bina Insani, Indonesia)

Technical Team

Jafar Shadiq (Universitas Bina Insani, Indonesia)

Mardi Yudhi Putra (Universitas Bina Insani, Indonesia)

Ari Nurul Alfian (Universitas Bina Insani, Indonesia)

Technical Program Committee

Intan Ermahani A. Jalil	Universiti Teknikal Malaysia Melaka	Malaysia
Zainul Abidin	Universitas Brawijaya	Indonesia
Sukarya Ade	Indonesian Researcher and Scientist Institute	Indonesia
I Adiyasa	Gadjah Mada University	Indonesia
Naveen Aggarwal	Panjab University	India
Mohd Ashraf Ahmad	Universiti Malaysia Pahang	Malaysia
Luis Alves	Polytechnic Institute of Bragança	Portugal
Yosua Alvin Adi Soetrisno	Diponegoro University	Indonesia
Lala Hucadinota Ainul Amri	Politeknik Negeri Madiun	Indonesia
Widyastuti Andriyani	Universitas Teknologi Digital Indonesia	Indonesia
Abul Al Arabi	Texas A&M University	USA
Rita Arifin	Bina Insani University	Indonesia
Andria Arisal	Indonesian Institute of Sciences	Indonesia
Mohd Rosli Arshad	University Kuala Lumpur	Malaysia
Hilmi Aulawi	Institut Teknologi Garut	Indonesia
Asrul Izam Azmi	Universiti Teknologi Malaysia	Malaysia
Nanang Cahyana	Bandung Institute of Technology	Indonesia
Alessandro Carrega	UNIGE	Italy
Saad Chakkor	University of Abdelmalek Essaâdi	Morocco
Voeun Chan	Institute of Technical	Cambodia
Ahmad Chusyairi	Universitas Bina Insani	Indonesia
Akhmad Dahlan	Universitas Amikom Yogyakarta	Indonesia

George Dekoulis	Neapolis University Pafos	Cyprus
Arif Djunaidy	Institut Teknologi Sepuluh Nopember	Indonesia
Andi Wahyu Rahardjo Emanuel	Universitas Atma Jaya Yogyakarta	Indonesia
Akaa Eteng	University of Port Harcourt	Nigeria
Ahmad Fajar	Bina Nusantara University	Indonesia
Arna Fariza	Politeknik Elektronika Negeri Surabaya	Indonesia
Aashish Gadgil	KLS Gogte Institute of Technology, Belgaum	India
Akhil Gupta	Lovely Professional University	India
Ibnu Hadi Purwanto	Universitas AMIKOM Yogyakarta	Indonesia
Seng Hansun	Universitas Multimedia Nusantara	Indonesia
Richki Hardi	Universitas Mulia	Indonesia
Sri Hartati	Gadjah Mada University	Indonesia
Hanny Haryanto	Universitas Dian Nuswantoro	Indonesia
Henderi Henderi	University of Raharja	Indonesia
Fajar Hermawati	Universitas 17 Agustus 1945 Surabaya	Indonesia
Roberto Carlos Herrera Lara	Electricity Company of Quito	Ecuador
M Heryanto	Universitas Dian Nuswantoro	Indonesia
Hozairi Hozairi	Universitas Islam Madura	Indonesia
Paulus Insap Santosa	Universitas Gadjah Mada	Indonesia
Iswandi Iswandi	Gadjah Mada University	Indonesia
Ramkumar Jaganathan	Dr NGP Arts and Science College	India
Lie Jasa	Udayana University	Indonesia
Mohammed Kaabar	Washington State University	USA

Wasnaa Kadhim	University of Information Technology and Communications	Iraq
Ahmed Kawther	Mustansiriyah Universtiy	Iraq
Reza Khalilian	MUI Research Assistant and Author	Iran
Channa Khieng	National Polytechnic Institute of Cambodia	Cambodia
Sandy Kosasi	STMIK Pontianak	Indonesia
Domy Kristomo	Universitas Gadjah Mada	Indonesia
Domy Kristomo	Universitas Teknologi Digital Indonesia	Indonesia
Dede Kurniadi	Institut Teknologi Garut	Indonesia
Beomseok Lee	Chung-Ang University	Korea (South)
Xia Li	Apple	USA
Pavel Loskot	ZJU-UIUC Institute	China
Mustafa Man	University Malaysia Terengganu	Malaysia
Maslin Masrom	UniversitiTeknologi Malaysia	Malaysia
Ratheesh Kumar Meleppat	University of California Davis	USA
Dan Milici	University of Suceava	Romania
Mohammed Mohammed	University of Technology, Baghdad	Iraq
Nor Liyana Mohd Shuib	University of Malaya	Malaysia
Intan Mutia	IPB University	Indonesia
Hea Choon Ngo	Universiti Teknikal Malaysia Melaka	Malaysia
Muhammad Agung Nugroho	Universitas Teknologi Digital Indonesia	Indonesia
Nurdin Nurdin	Universitas Islam Negeri Datokarama Palu	Indonesia
Nitish Ojha	Sharda University, Greater Noida, UP	India
Ilker Ali Ozkan	Selcuk University	Turkey

Andrew Pakpahan	Jl. Kolonel Masturi No. 288	Indonesia
Alvaro Paricio García	Universidad de Alcalá	Spain
Shashikant Patil	Mumbai University	India
Sutarman PhD	Magister of Information Technology University Technology of Yogyakarta	Indonesia
Kiran Sree Pokkuluri	Shri Vishnu Engineering College for Women(A)	India
Irfan Pratama	Universitas Mercubuana Yogyakarta	Indonesia
Edy Prayitno	Universitas Teknologi Digital Indonesia	Indonesia
Tri Priyambodo	Universitas Gadjah Mada	Indonesia
Nila Puspitasari	Universitas AMIKOM Yogyakarta	Indonesia
Ali Rafiei	General Motors	Canada
Grienggrai Rajchakit	Maejo University	Thailand
Priya Ranjan	Bhubaneshvar Institute of Technology	India
Rasim Rasim	Indonesia University of Education	Indonesia
Zairi Ismael Rizman	Universiti Teknologi MARA	Malaysia
Dedi Rohendi	Universitas Pendidikan Indonesia	Indonesia
Heru Agus Santoso	Dian Nuswantoro University	Indonesia
Syantam Sarkar	MVJ College of Engineering	India
Enny Sela	Universitas Teknologi Yogyakarta	Indonesia
Ni Wayan Parwati Septiani	Universitas Indraprasta PGRI Jakarta	Indonesia
Anindita Septiarini	Universitas Mulawarman	Indonesia
Bayu Setiaji	Universitas AMIKOM Yogyakarta	Indonesia
Iwan Setyawan	Satya Wacana Christian University	Indonesia
Aditi Sharma	Parul University, Vadodara	India

Poorani Shivkumar	ESEC	India
Neeraj Singh	LTTS	India
Karthik Sivarama Krishnan	Rochester Institute of Technology	USA
lickho Song	Korea Advanced Institute of Science and Technology	Korea (South)
Yi-Jen Su	Shu-Te University	Taiwan
Joey Suba	University of the Assumption	Philippines
Suharjito Suharjito	Bina Nusantara University	Indonesia
Cucut Susanto	Universitas Dipa Makassar	Indonesia
Chakib Taybi	Mohammed First University	Morocco
Dewi Tresnawati	Institut Teknologi Garut	Indonesia
Evi Triandini	Institut Teknologi dan Bisnis STIKOM Bali	Indonesia
Tram Truong-Huu	Singapore Institute of Technology (SIT)	Singapore
Terlapu Vital	jntuK	India
Jeng-Feng Weng	NationalUnited University	Taiwan
Ferry Wahyu Wibowo	Universitas Amikom Yogyakarta	Indonesia
Widodo Widodo	Universitas Negeri Jakarta	Indonesia
Wihayati Wihayati	Satya Wacana Christian University	Indonesia
Beihao Xia	Huazhong University of Science and Technology	China
Warusia Yassin	Universiti Teknikal Malaysia Melaka	Malaysia
Thaweesak Yingthawomsuk	King Mongkut's University of Technology Thonburi	Thailand
Ali Zalzala	Community Tracks Ltd	United Kingdom (Great Britain)
Nur Zareen Zulkarnain	Universiti Teknikal Malaysia Melaka	Malaysia

Additional Reviewers

Zainul Abidin	Universitas Brawijaya	Indonesia
I Wayan Adiyasa	Gadjah Mada University	Indonesia
Mohd Ashraf Ahmad	Universiti Malaysia Pahang	Malaysia
Luis M. Alves	Polytechnic Institute of Bragança	Portugal
Lala Hucadinota Ainul Amri	Politeknik Negeri Madiun	Indonesia
Andria Arisal	Indonesian Institute of Sciences	Indonesia
Mohd Rosli Arshad	University Kuala Lumpur	Malaysia
Hilmi Aulawi	Institut Teknologi Garut	Indonesia
Asrul Izam Azmi	Universiti Teknologi Malaysia	Malaysia
Alessandro Carrega	UNIGE	Italy
Voeun Chan	Institute of Technical	Cambodia
Andi Wahyu Rahardjo Emanuel	Universitas Atma Jaya Yogyakarta	Indonesia
Arna Fariza	Politeknik Elektronika Negeri Surabaya	Indonesia
Ibnu Hadi Purwanto	Universitas AMIKOM Yogyakarta	Indonesia
Seng Hansun	Universitas Multimedia Nusantara	Indonesia
Sri Hartati	Gadjah Mada University	Indonesia
Hanny Haryanto	Universitas Dian Nuswantoro	Indonesia
Henderi Henderi	University of Raharja	Indonesia
Fajar Astuti Hermawati	Universitas 17 Agustus 1945 Surabaya	Indonesia
Ramkumar Jaganathan	Dr NGP Arts and Science College	India
Wasnaa Kadhim	University of Information Technology and Communications	Iraq
Ahmed Kawther	Mustansiriyah Universtiy	Iraq
Reza Khalilian, Engineer	MUI Research Assistant and Author	Iran
Channa Khieng	National Polytechnic Institute of Cambodia	Cambodia
Sandy Kosasi	STMIK Pontianak	Indonesia
Dede Kurniadi	Institut Teknologi Garut	Indonesia
Beomseok Lee	Chung-Ang University	Korea (South)
Xia Li	Apple	USA
Maslin Masrom	UniversitiTeknologi Malaysia	Malaysia
Ratheesh Kumar Meleppat	University of California Davis	USA

Dan L. Milici	University of Suceava	Romania
Intan Mutia	IPB University	Indonesia
Muhammad Agung Nugroho	Universitas Teknologi Digital Indonesia	Indonesia
Nurdin Nurdin	Universitas Islam Negeri Datokarama Palu	Indonesia
Shashikant S. Patil	Mumbai University	India
Irfan Pratama	Universitas Mercubuana Yogyakarta	Indonesia
Edy Prayitno	Universitas Teknologi Digital Indonesia	Indonesia
Tri K Priyambodo	Universitas Gadjah Mada	Indonesia
Grienggrai Rajchakit	Maejo University	Thailand
Priya Ranjan	Bhuvaneshvar Institute of Technology	India
Rasim Rasim	Indonesia University of Education	Indonesia
Ni Wayan Parwati Septiani	Universitas Indraprasta PGRI Jakarta	Indonesia
Bayu Setiaji	Universitas AMIKOM Yogyakarta	Indonesia
Iwan Setyawan	Satya Wacana Christian University	Indonesia
Aditi Sharma	Parul University, Vadodara	India
Neeraj Kumar Singh	LTTS	India
Karthik Sivarama Krishnan	Rochester Institute of Technology	USA
lickho Song	Korea Advanced Institute of Science and Technology	Korea (South)
Yi-Jen Su	Shu-Te University	Taiwan
Suharjo Suharjo	Bina Nusantara University	Indonesia
Cucut Susanto	Universitas Dipa Makassar	Indonesia
Dewi Tresnawati	Institut Teknologi Garut	Indonesia
Evi Triandini	Institut Teknologi dan Bisnis STIKOM Bali	Indonesia
Terlapu Pandu Ranga Vital	jntuK	India
Jeng-Feng Weng	NationalUnited University	Taiwan
Widodo Widodo	Universitas Negeri Jakarta	Indonesia
Wihayati Wihayati	Satya Wacana Christian University	Indonesia
Thaweesak Yingthawornsuk	King Mongkut's University of Technology Thonburi	Thailand
Nur Zareen Zulkarnain	Universiti Teknikal Malaysia Melaka	Malaysia

3. Daftar Isi, Artikel Penulis

Manurung, Jonson	1.9.7	478	<i>Comparative Models of Price Estimation Using Multiple Linear Regression and Random Forest Methods</i>
Maralit, Alexander II	2.4.5	691	<i>QueenBuzz: A CNN-based architecture for Sound Processing of Queenless Beehive Towards European Apis Mellifera Bee Colonies' Survivability</i>
Maralit, Cynthia Jane	1.8.4	410	<i>Design and Development of the Real-Time Wireless Antenna Misalignment Detection System</i>
	1.8.5	416	<i>Design and Development of the Real-Time Antenna Misalignment Detection System</i>
	1.8.6	422	<i>Design and Development of the Real-Time Wired Antenna Misalignment Detection System</i>
Mardison, Mardison	1.5.1	222	<i>Detection of Kidney Cysts of Kidney Ultrasound Image using Hybrid Method: KNN, GLCM, and ANN Backpropagation</i>
Mardiyono, Anggi	1.8.2	398	<i>Implementation of Convolutional Neural Network for COVID19 Screening using X-Rays Images</i>
Marliani, Marliani	1.3.7	146	<i>Implementation of wild horse optimization (WHO) method for optimal hybrid renewable energy designs</i>
Martati, Martati	2.8.6	915	<i>The Economic Impact on Energy Management in Hybrid Street Lights Solar Panel System and 220VAC Grid</i>
Maryani, Maryani	1.6.2	284	<i>Human Resources Management Information System Requirement Analysis and Development in Humanitarian Foundation</i>
Maulana, Fairuz	2.1.3	506	<i>Development of Real-Time Face Recognition for Smart Door Lock Security System using Haar Cascade and OpenCV LBPH Face Recognizer</i>
Maulana, Helmi	2.1.5	517	<i>Simple Additive Weighting (SAW) in the Development of a Decision Support System for the Selection of House Construction Project Teams</i>
Mawardi, Viny	1.1.4	17	<i>Discord Bot Design for Hate Speech Sensor Using Convolutional Neural</i>

Detection of Kidney Cysts of Kidney Ultrasound Image using Hybrid Method: KNN, GLCM, and ANN Backpropagation

1st Mardison
Computer System
Computer Science Faculty
Universitas Putra Indonesia YPTK
Padang, Indonesia
mardison@upiypk.ac.id

2nd Yuhandri
Information Technology
Computer Science Faculty
Universitas Putra Indonesia YPTK
Padang, Indonesia
yuyu@upiypk.ac.id

Abstract—This research is aim to detect kidney cysts from human kidney Ultrasound (USG) 2D Images. This research uses data from Hospital patients as many as 25 Ultrasound images of the human kidney in the format image .jpg. This research uses the K-Nearest Neighbor (KNN) method for image classification of ultrasound images then using Gray Level Co-Occurrence Matrix (GLCM) method for image extraction to detect cyst and non-cyst regions from the result of classification after that using Artificial Neural Network (ANN) method type Backpropagation for image detection to find cysts from human kidney Ultrasound (USG) 2D Image from the result of image extraction. The result of this research is producing the algorithm to implement the method and the tool software application to detect kidney cysts from ultrasound 2D images. The accuracy of this tool is 84% which can detect with accurate 21 kidney cysts from 25 kidney ultrasound 2D images that validate of a Urology Specialist Doctor.

Keywords—ultrasound (USG) 2D Image, kidney cysts, KNN method, GLCM method, ANN type Backpropagation method.

I. INTRODUCTION

Digital image processing (DIP) is one of the branches of science in the field of computer science that studies techniques or methods for processing images in digital format [1]–[4]. The image referred to here is a still image (photo) and a moving image (derived from the camera). While digital here means that image processing is done digitally using a computer. Mathematically, the image is a continuous function with light intensity in a two-dimensional plane. To be processed by a digital computer, an image must be presented numerically with discrete values. The representation of a continuous function into discrete values is called image digitization.

Along with the development of technology and information today, the digital image is a very important thing. Digital images have been widely used in various fields, one of which is the health sector [5]–[9]. In the field of Health, digital images are used to take pictures of the condition of human organs when they are in the human body that is not directly visible to the eyes of a doctor. There are many digital imaging technologies of the human body in the world of Health such as ultrasound digital images, Rongen digital images, X-Ray digital images, CT Scan digital images, and MRI digital images. Each type of digital image has its advantages and disadvantages.

The urinary system consists of three parts: the kidneys, the bladder, the ureters, and the urethra (urinary tract). Each part of the urinary system has its function and role. One of the organs of the human body that is very important in the

urinary system is the kidney. Kidneys function as organs that function to filter and dispose of waste in the human body, such as toxins, excess salt, and urea (nitrogen-containing waste resulting from protein metabolism) [10]–[13]. Urea formed in the body is transported through the blood to the kidneys for disposal. Without kidneys, waste and toxins would accumulate in the blood.

Ultrasonography or better known as ultrasound is a technology for capturing images of the human body and is widely used in the medical world [14]–[16]. One of the organs of the human body can be captured using kidney ultrasound technology. This is done to find out what disease occurs in the kidney. Ultrasound images are divided into several types, namely 2D, 3D, and 4D ultrasound images. 2D ultrasound is a type of examination that uses 2-dimensional technology in which the imaging results are flat black and white images.

Previous research was conducted by Paladugu Raju et al in 2020 [17] who detected and segmented kidney cysts and tumors using the Optimal GLCM method combined with FCM. This study uses data in the form of ultrasound images of the kidneys which are transformed as 3×3 blocks and the attribute is omitted. The analysis in this study is that the proposed process is augmented when contrasted with the obtained process through different metrics such as sensitivity, specificity, accuracy, Positive Predictive Value (PPV), and Negative Predictive Value (NPV). The results of this study are the sensitivity, specificity, and accuracy of the proposed FB-FCM-WOA (91.1%, 98.6%, and 98.4%) than the obtained process. PPV and NPV (71.8% and 99.6%) were also better than the obtained process.

Another study conducted by Qiang Zheng et al in 2021 [18] conducted a dynamic graph-cutting method with integrated feature maps for kidney segmentation in 2D ultrasound images. This study used data in the form of 2D ultrasound images of the kidneys from 85 subjects. Imaging data from 20 randomly selected subjects were used as training data to set the parameters of the image segmentation method, and the remaining data were used as test data for validation. The analysis in this study is to compare our method with image segmentation methods, such as LRAC, GAC, and AMFSM. The results of this study are the proposed method obtains promising segmentation results for bilateral kidneys (Mean dice index = 0.9446, average distance = 2.2551, average specificity = 0.9971, average accuracy -mean = 0.9919), better than the other methods compared ($P < 0.05$, paired Wilcoxon rank count test).

The USG image produced by ultrasound technology is still in the form of a black and white image that is not clear

or blurry so that ordinary people or people who do not know in the field of medicine cannot read what is displayed by the ultrasound image [19], [20]. A doctor who specializes in Urology has expertise in reading and translating the results of ultrasound images in the human kidney. The quality of the results of reading or translating ultrasound images from a urology specialist depends on the quality of the ultrasound images captured from the human body. The better and clearer the ultrasound image, the more precise and accurate the results of reading and translation by the doctor will be so that the diagnosis of a person's disease becomes very precise. Under these conditions, it is better if the image produced by the ultrasound can be improved to be clearer and more detailed so that the reading results become more precise and accurate.

At the moment, based on a discussion with a Urology specialist in Padang City, it is stated that a Urology specialist is still unable to detect cyst objects that have cysts in the human kidney only based on 2D ultrasound images because the images produced by 2D ultrasound are still blurry, and less clear. A more accurate detection to detect Kidney Cysts is by taking a CT (Computed Tomography) Scan image of the human kidney. However, the cost required to perform a CT-Scan is very large, plus not all hospitals (RS) in Indonesia have CT-Scan machines because the price of the CT Scan machine is very expensive.

More specifically, based on a search for reputable international journals and impact factors, currently, there are no researchers who have tried to detect Multiple Kidney Cysts known as Multiple Kidney Cysts (Multiple Kidney Cysts). If the results of 2D Kidney Ultrasound (Ultrasonography) images can be as good and as good as CT (Computed Tomography) Scans of human kidneys in detecting Multiple Kidney Cysts, it will be very helpful for the medical world, especially in the field of Urology in detecting the disease and also very helpful for hospitals that serve the treatment of diseases. Urology especially kidney and is very helpful for patients suffering from kidney disease. In this study, the Hough transform and GLCM methods were developed to detect multiple kidney cysts automatically based on 2D ultrasound (ultrasonography) images of human kidneys. The data used to validate the results of this study is the data from the CT-Scan image of the human kidney.

II. METHODOLOGY

A. Research Framework

This research collects the data input in the form of an Ultrasound (USG) Image of a Kidney that has Multiple Cysts. Then processing that data image using K-Nearest Neighbors (KNN) Method after that using GLCM Method and lastly using the Artificial Neural Network (ANN). The research framework can be seen in figure 1 below.

B. Research Framework details

The first step of this research is to collect the data input. The input data is a very important thing for research because this is the resource problem that will be solved. The data input of this research is the Ultrasound (USG) image of the Human Kidney. The USG kidney image is on the left and right sides of a human kidney. The number of pictures that are collected is 40 kidney USG images. The 40 kidney USG

images intend to get better results in detecting cysts of the kidney. The format file of USG Image of Kidney is. JPG. The USG kidney image that collected using an ultrasound image capture machine. All of the images are from a general hospital in Padang City, West Sumatera Province, Indonesia.




Fig. 1. Research Framework

The second step of this research is image classification. Image classification intends to partition an image into non-overlapping regions with homogeneous characteristics, such as intensity, color, and texture. In this image classification in this research using K-Nearest Neighbors (KNN) Method. KNN method uses the Euclidean value distance in the calculation of the image data. The Euclidean distance between each segment in the segmentation image and each training region that you specify is calculated using the K Nearest Neighbor (KNN) approach. In n-dimensional space, where n is the number of attributes for that training zone, the distance is measured. The KNN method algorithm is followed [21]–[25]:

1. Step 1: Select the number K of the neighbors
2. Step 2: Calculate the euclidean distance of K number of neighbors using the formula below:

$$d = \sqrt{(x_2 - x_1)^2 + (y_2 - y_1)^2} \quad (1)$$

Where: d is euclidean distance, x_1 and x_2 is two points in a two-dimensional x axis, y_1 and y_2 is two points in a two-dimensional y axis.

3. Step 3: Take the K nearest neighbors as per the calculated Euclidean distance.
4. Step 4: Among these k neighbors, count the number of the data points in each category.
5. Step 5: Assign the new data points to that category for which the number of neighbors is maximum.
6. Step 6: Our model is ready.

The third step of this research is image extraction. The data resulting from the image segmentation process of the second step before. To do image extraction in this research using the GLCM method to detect cyst and non-cyst regions. The image implementation process is carried out, namely clarifying the object to be studied in the image by performing calculations to reverse the value in the binary image. After the image implementation process is carried out, then perform an Open Area BW aimed at estimating the area of the binary image object. The GLCM method algorithm is followed [26]–[28]:

1. Step 1: Quantize the image data. Each sample on the echogram is treated as a single image pixel and the value of the sample is the intensity of that pixel. These intensities are then further quantized into a specified number of discrete gray levels as specified under Quantization.
2. Step 2: Create the GLCM. It will be a square matrix $N \times N$ in size where N is the Number of levels specified under Quantization. The matrix is created as follows:
 - Let s be the sample under consideration for the calculation.
 - Let W be the set of samples surrounding sample s that fall within a window centered upon sample s of the size specified under Window Size.
 - Considering only the samples in the set W , define each element i, j of the GLCM as the number of times two samples of intensities i and j occur in a specified Spatial relationship (where i and j are intensities between 0 and Number of levels-1).
 - The sum of all the elements i, j of the GLCM will be the total number of times the specified spatial relationship occurs in W .
 - Make the GLCM symmetric:
 - Make a transposed copy of the GLCM
 - Add this copy to the GLCM itself
 - This produces a symmetric matrix in which the relationship i to j is indistinguishable from the relationship j to i (for any two intensities i and j). As a consequence, the sum of all the elements i, j of the GLCM will now be twice the total number of times the specified spatial relationship occurs in W (once where the sample with intensity i is the reference sample and once where the sample with intensity j is the reference sample), and for any given i , the sum of all the elements i, j with the given i will be the total number of times a sample of intensity i appears in the specified spatial relationship with another sample.
 - Normalize the GLCM:
 - Divide each element by the sum of all elements. The elements of the GLCM may now be considered probabilities of finding the relationship i, j (or j, i) in W .

3. Calculate the selected Feature. This calculation uses only the values in the GLCM. The formula is as followed:

$$Shade = \text{sgn}(A) |A|^{\frac{1}{3}} \quad (2)$$

Where: $Shade$ is shade value, $\text{sgn}(A)$ is a sign of a real number

4. The sample s in the resulting virtual variable are replaced by the value of this calculated feature.

The fourth step of this research is image detection. Image detection is the process of categorizing and labeling groups of pixels or vectors within an image based on specific rules. The categorization law can be devised using one or more spectral or textural characteristics. The result data of image extraction is used from the GLCM method. To do image detection in this research using Artificial Neural Network (ANN) method type Backpropagation. It can improve ultrasound images, to detect Kidney Cysts. This helps Urology Specialists and related Hospitals in using the Ultrasound Machine Optimally. The ANN method type Backpropagation algorithm is followed [29]–[32]:


1. Step 1: Prepare the data set, which is the source of information for the classification problem. he following concepts—Data source, Variables, and Instances—need to be configured in order to achieve that.
2. Step 2: Choose the correct neural network architecture. for classification problems, it is usually composed of: A scaling layer, Two perceptron layers, and A probabilistic layer.
3. Step 3: Set the training strategy, which is composed of: Loss index, Optimization algorithm.
4. Step 4: Set the model selection, which is composed of: The inputs selection algorithm, Neurons selection algorithm.

The result of this research is can be seen which part is a kidney cyst on the ultrasound image of the kidney automatically without the need for a diagnosis from a doctor and the accuracy of the detection results is the same as that done by a doctor and or by a CT scan of the kidneys.

III. RESULT AND DISCUSSION

A. Data Collection

Step 1. Data is gathered from an ultrasound image. A total of 25 USG pictures of a human kidney make up this image. Cysts should be visible in the USG images of the human kidney. As a result of this procedure, the software now has the data needed to perform ultrasound (USG) image classification. The K-Nearest Neighbors (KNN) Method using to solve this problem. Four USG scans of the kidneys used in this study are shown in Figure 2 below:






Fig. 2. Data Collection Kidney USG Image a, b, c, d

The following Algorithm 1 shows the algorithm that employs to gather data from 4 kidney USG images using MATLAB software:

Algorithm 1: Read Data Collection

```

start
clc; clear; close all; warning off all;
% set the folder name
nama_folder = 'Citra Kista Ginjal';
% read filenames with the extension .jpeg
nama_file = dir(fullfile(nama_folder, '*.jpg'));
% read number of files
jumlah_file = numel(nama_file);
% processing all files
for k = 1:jumlah_file
% read image files
Img = imread(fullfile(nama_folder, nama_file(k).name));
end

```

B. Process

Step 2. After collecting four Kidney USG Images then doing image classification of the USG kidney image using the K-Nearest Neighbors (KNN) Method. The algorithm used to classify the four kidney USG images using the MATLAB application can be seen in Algorithm 2 below:

Algorithm 2: image classification using K-Nearest Neighbors (KNN) Method

```

start
% convert rgb image color space to grayscale
Img_gray = double(rgb2gray(Img));
% call the training result network
load jaringan
% read output clusters
[row,col] = size(Img_gray);
x = reshape(Img_gray,row*col,1);
y = predict(Mdl,x);
% compile the clustering result image
Img2 = zeros(row,col);
for n = 1:numel(Img2)
if isequal(y{n}, 'region 1')
Img2(n) = 1;
elseif isequal(y{n}, 'region 2')
Img2(n) = 2;
elseif isequal(y{n}, 'region 3')
Img2(n) = 3;
end
end

```

The resulting image of image classification using algorithm 2 above can be seen in figure 3 below:




Fig. 3. Result in Image Classification of Kidney USG Image a, b, c, d

Step 3. After image extraction then use Gray Level Co-Occurrence Matrix (GLCM) method to Detect Cyst and Non-Cyst Regions. The algorithm used to extract from the result of image classification using MATLAB application can be seen in Algorithm 3 below:

Algorithm 3: image extraction from image extraction result using Gray Level Co-Occurrence Matrix (GLCM)

```

start
% look for the region of the kidney cyst
bw = Img2==1;
% perform morphological operations
bw = imclearborder(bw);
bw = imfill(bw,'holes');
bw = bwareaopen(bw,100);
% extensive feature extraction
cc = bwconncomp(bw,8);
s = regionprops(cc); Area = cat(1,s.Area);
% GLCM feature extraction
[B,L] = bwlabel(bw);
ciri_uji = []; for m = 1:L
bw2 = B==m;
[row,col] = find(bw2==1);
Img_gray2 = Img_gray;
Img_gray2(~bw2) = 0;
Img_crop = imcrop(Img_gray2,[min(col), min(row), max(col)-min(col),... max(row)-min(row)]);
pixel_dist = 1;
GLCM = graycomatrix(Img_crop,'Offset',[0 pixel_dist,... -pixel_dist pixel_dist; -pixel_dist 0;... -pixel_dist -pixel_dist]);
stats = graycoprops(GLCM, {'contrast','correlation',... 'energy','homogeneity'});
Contrast = mean(stats.Contrast); Correlation = mean(stats.Correlation);
Energy = mean(stats.Energy); Homogeneity = mean(stats.Homogeneity);
ciri = [Area(m),Contrast,Correlation,Energy,Homogeneity];
% construct test features
ciri_uji = [ciri_uji;ciri];
end

```

The resulting image of image extraction using algorithm 3 above can be seen in figure 4 below:




Fig. 4. Result in Image Extraction of Kidney USG Image a, b, c, d

Step 4. After image extraction then image detection using Artificial Neural Network (ANN) method type Backpropagation based on the input value of the GLCM method result. The algorithm used to detect kidney cysts from the result of image extraction using MATLAB application can be seen in Algorithm 4 below:

```

Algorithm 4: image classification from image extraction
result using the Artificial Neural Network (ANN) method
start
% transpose the test feature
ciri_uji = ciri_uji';
% read network output value
nilai_keluaran = round(sim(jaringan,ciri_uji));
% look for the index region of kidney cysts
[-,n] = find(nilai_keluaran==1);
% displays the segmented image
bw3 = false(size(bw));
for i = 1:numel(n)
bw3(cc.PixelIdxList{n(i)}) = true;
R = img(:,:,1);
G = img(:,:,2);
B = img(:,:,3);
R(bw3) = 255;
G(bw3) = 255;
B(bw3) = 0;
RGB = cat(3,R,G,B);
% display image
Figure; subplot(1,2,1)
imshow(img,[]);
title('Citra Asli');
subplot(1,2,2);
imshow(RGB,[])
title('Hasil Segmentasi');
end

```

The resulting image of image detection using algorithm 3 above can be seen in figure 5 below:





Fig. 5. Result in Image Detection of Kidney USG Image a, b, c, d

IV. CONCLUSION

The K-Nearest Neighbors (KNN) method used to classify 2D Kidney ultrasound images that are input into the program data works very properly and accurately classifies which parts of the image are kidney cysts and which parts are not kidney cysts. The image data that have been classified are then extracted using the Gray Level Co-Occurrence Matrix (GLCM) method to obtain image characteristics which are the area of the kidney cyst and not the area of the kidney cyst. This method can also work properly and accurately. After obtaining data extraction of kidney cyst areas with non-kidney cyst areas, the data was used to detect kidney cysts using the Backpropagation type Artificial Neural Network (ANN) method. This method can also work properly and accurately. Overall the performance of the program which is made from the 25 2D ultrasound images of the kidneys tested resulted in 21 images that could detect well and accuracy of the presence of kidney cysts of 84%. These results have been validated by a specialist urologist. For future or prospective of this work could be extended for the imaging techniques such as Optical coherence tomography (OCT), which is an optical counter part of the ultrasound imaging, as a potential future scope/

REFERENCES

- [1] G. U. Kaya and T. Ö. Onur, "Genetic algorithm based image reconstruction applying the digital holography process with the Discrete Orthonormal Stockwell Transform technique for diagnosis of COVID-19," *Comput. Biol. Med.*, vol. 148, no. August, p. 105934, 2022, doi: 10.1016/j.combiomed.2022.105934.
- [2] N. Geier, G. Póka, Á. Jacsó, and C. Pereszlai, "A method to predict drilling-induced burr occurrence in chopped carbon fibre reinforced polymer (CFRP) composites based on digital image processing," *Compos. Part B Eng.*, vol. 242, no. December 2021, p. 110054, 2022, doi: 10.1016/j.compositesb.2022.110054.
- [3] G. Póka and B. Z. Balázs, "A robust digital image processing method for measuring the planar burr length at milling," *J. Manuf. Process.*, vol. 80, no. October 2021, pp. 706-717, 2022, doi: 10.1016/j.jmapro.2022.06.037.
- [4] O. Angel, G. Rothwell, R. English, J. Ren, and A. Cummings, "Effect of post processing of digital image correlation on obtaining accurate true stress-strain data for AISI 304L," *Nucl. Eng. Technol.*, no. xxxx, 2022, doi: 10.1016/j.net.2022.03.038.
- [5] S. Iyanna, P. Kaur, P. Raghavan, S. Talwar, and A. K. M. N. Islam, "Digital transformation of healthcare sector - What is impeding adoption and continued usage of technology-driven innovations by end-users?," *J. Bus. Res.*, vol. 153, no. August, pp. 150-161, 2022, doi: 10.1016/j.jbusres.2022.08.007.
- [6] M. Alhasan and M. Hasanien, "Digital imaging, technologies and artificial intelligence applications during COVID-19 pandemic," *Comput. Med. Imaging Graph.*, vol. 91, no. December 2020, p. 101933, 2021, doi: 10.1016/j.compmedimag.2021.101933.
- [7] E. Mbugue, B. Muchemwa, S. Jiyane, and J. Batani, "Sensors and healthcare 5.0: transformative shift in virtual care through emerging digital health technologies," *Glob. Heal. J.*, vol. 5, no. 4, pp. 169-177, 2021, doi: 10.1016/j.glohj.2021.11.008.
- [8] E. Mbugue, J. Batani, G. Gaobotse, and B. Muchemwa, "Virtual




Fig. 4. Result in Image Extraction of Kidney USG Image a, b, c, d

Step 4. After image extraction then image detection using Artificial Neural Network (ANN) method type Backpropagation based on the input value of the GLCM method result. The algorithm used to detect kidney cysts from the result of image extraction using MATLAB application can be seen in Algorithm 4 below:

Algorithm 4: image classification from image extraction result using the Artificial Neural Network (ANN) method

```

start
% transpose the test feature
ciri_uji = ciri_uji';
% read network output value
nilai_keluaran = round(sim(jaringan,ciri_uji));
% look for the index region of kidney cysts
[~,n] = find(nilai_keluaran==1);
% displays the segmented image
bw3 = false(size(bw));
for i = 1:numel(n)
bw3(cc.PixelsIdxList{n(i)}) = true;
R = Img(:,:,1);
G = Img(:,:,2);
B = Img(:,:,3);
R(bw3) = 255;
G(bw3) = 255;
B(bw3) = 0;
RGB = cat(3,R,G,B);
% display image
Figure; subplot(1,2,1)
imshow(Img,[]);
title('Citra Asli');
subplot(1,2,2);
imshow(RGB,[])
title('Hasil Segmentasi');
end

```

The resulting image of image detection using algorithm 3 above can be seen in figure 5 below:





Fig. 5. Result in Image Detection of Kidney USG Image a, b, c, d

IV. CONCLUSION

The K-Nearest Neighbors (KNN) method used to classify 2D Kidney ultrasound images that are input into the program data works very properly and accurately classifies which parts of the image are kidney cysts and which parts are not kidney cysts. The image data that have been classified are then extracted using the Gray Level Co-Occurrence Matrix (GLCM) method to obtain image characteristics which are the area of the kidney cyst and not the area of the kidney cyst. This method can also work properly and accurately. After obtaining data extraction of kidney cyst areas with non-kidney cyst areas, the data was used to detect kidney cysts using the Backpropagation type Artificial Neural Network (ANN) method. This method can also work properly and accurately. Overall the performance of the program which is made from the 25 2D ultrasound images of the kidneys tested resulted in 21 images that could detect well and accuracy of the presence of kidney cysts of 84%. These results have been validated by a specialist urologist. For future or prospective of this work could be extended for the imaging techniques such as Optical coherence tomography (OCT), which is an optical counter part of the ultrasound imaging, as a potential future scope/

REFERENCES

- [1] G. U. Kaya and T. Ö. Onur, "Genetic algorithm based image reconstruction applying the digital holography process with the Discrete Orthogonal Stockwell Transform technique for diagnosis of COVID-19," *Comput. Biol. Med.*, vol. 148, no. August, p. 105934, 2022, doi: 10.1016/j.compbiomed.2022.105934.
- [2] N. Geier, G. Póka, Á. Jászó, and C. Pereszlai, "A method to predict drilling-induced burr occurrence in chopped carbon fibre reinforced polymer (CFRP) composites based on digital image processing," *Compos. Part B Eng.*, vol. 242, no. December 2021, p. 110054, 2022, doi: 10.1016/j.compositesb.2022.110054.
- [3] G. Póka and B. Z. Balázs, "A robust digital image processing method for measuring the planar burr length at milling," *J. Manuf. Process.*, vol. 80, no. October 2021, pp. 706–717, 2022, doi: 10.1016/j.jmapro.2022.06.037.
- [4] O. Angel, G. Rothwell, R. English, J. Ren, and A. Cummings, "Effect of post processing of digital image correlation on obtaining accurate true stress-strain data for AISI 304L," *Nucl. Eng. Technol.*, no. xxxx, 2022, doi: 10.1016/j.net.2022.03.038.
- [5] S. Iyanna, P. Kaur, P. Rathan, S. Talwar, and A. K. M. N. Islam, "Digital transformation of healthcare sector - What is impeding adoption and continued usage of technology-driven innovations by end-users?," *J. Bus. Res.*, vol. 153, no. August, pp. 150–161, 2022, doi: 10.1016/j.jbusres.2022.08.007.
- [6] M. Alhasan and M. Hasanien, "Digital imaging, technologies and artificial intelligence applications during COVID-19 pandemic," *Comput. Med. Imaging Graph.*, vol. 91, no. December 2020, p. 101933, 2021, doi: 10.1016/j.compmedimag.2021.101933.
- [7] E. Mbunge, B. Muchemwa, S. Jiyane, and J. Batani, "Sensors and healthcare 5.0: transformative shift in virtual care through emerging digital health technologies," *Glob. Heal. J.*, vol. 5, no. 4, pp. 169–177, 2021, doi: 10.1016/j.glohj.2021.11.008.
- [8] E. Mbunge, J. Batani, G. Gaobotse, and B. Muchemwa, "Virtual

- healthcare services and digital health technologies deployed during coronavirus disease 2019 (COVID-19) pandemic in South Africa: a systematic review," *Glob. Heal. J.*, vol. 6, no. 2, pp. 102–113, 2022, doi: 10.1016/j.glohj.2022.03.001.
- [9] S. Wongvibulsin, T. M. Frech, M.-M. Chren, and E. R. Tkaczyk, "Expanding Personalized, Data-Driven Dermatology: Leveraging Digital Health Technology and Machine Learning to Improve Patient Outcomes," *JID Innov.*, vol. 2, no. 3, p. 100105, 2022, doi: 10.1016/j.xjidi.2022.100105.
- [10] J. Fabian *et al.*, "Articles Measurement of kidney function in Malawi, South Africa, and Uganda: a multicentre cohort study," *www.thelancet.com/lancetgh*, vol. 10, 2021, doi: 10.1016/S2214-109X(22)00239-X.
- [11] A. Akilu and C. Delgado, "The removal of race from kidney function estimation: Key points for primary providers," *J. Natl. Med. Assoc.*, vol. 114, no. 3, pp. S25–S33, 2022, doi: 10.1016/j.jnma.2022.05.008.
- [12] S. Geurts *et al.*, "Disentangling the association between kidney function and atrial fibrillation: a bidirectional Mendelian randomization study," *Int. J. Cardiol.*, vol. 355, no. January, pp. 15–22, 2022, doi: 10.1016/j.ijcard.2022.03.004.
- [13] J. Jefferis, A. Pelecanos, V. Catts, and A. Mallett, "The Heritability of Kidney Function Using an Older Australian Twin Population," *Kidney Int. Reports*, vol. 7, no. 8, pp. 1819–1830, 2022, doi: 10.1016/j.ekir.2022.05.012.
- [14] H. Nösslinger, E. Mair, H. Toplak, and M. Hörmann-Wallner, "Measuring subcutaneous fat thickness using skinfold calipers vs. high-resolution B-scan ultrasonography in healthy volunteers: A pilot study," *Clin. Nutr. Open Sci.*, vol. 41, pp. 19–32, 2022, doi: 10.1016/j.cunos.2021.11.007.
- [15] D. M. Pavlo *et al.*, "Pulsed Radiofrequency Rhizotomy of the Genicular Nerves of the Knee Guided by Radioscopy and Ultrasonography: Step-By-Step Technique," *Arthrosc. Tech.*, vol. 11, no. 3, pp. e391–e396, 2022, doi: 10.1016/j.eats.2021.11.006.
- [16] I. R. S. Lucena *et al.*, "A comparison between ultrasonography and single-phase computed tomography for preoperative assessment of solid abdominal tumors in children," *J. Pediatr. (Rio. J.)*, vol. 000, no. xxx, pp. 1–6, 2022, doi: 10.1016/j.jpeds.2022.05.003.
- [17] P. Raju, V. M. Rao, and B. P. Rao, "Optimal GLCM combined FCM segmentation algorithm for detection of kidney cysts and tumor," *Multimed. Tools Appl.*, vol. 78, no. 13, pp. 18419–18441, 2020, doi: 10.1007/s11042-018-7145-4.
- [18] Q. Zheng, S. Warner, G. Tasian, and Y. Fan, "A Dynamic Graph Cuts Method with Integrated Multiple Feature Maps for Segmenting Kidneys in 2D Ultrasound Images," *Acad. Radiol.*, vol. 25, no. 9, pp. 1136–1145, 2021, doi: 10.1016/j.acra.2018.01.004.
- [19] M. S. Alzabaidi *et al.*, "Towards deep observation: A systematic survey on artificial intelligence techniques to monitor fetus via Ultrasound Images," *arXiv*, vol. 25, no. 8, p. 104713, 2022, doi: 10.1016/j.jsci.2022.104713.
- [20] V. S. Mbbs, B. S. Mbbs, P. Hughes, M. B. Chb, and M. S. B. A. H., "Value of serial ultrasound imaging in conservative management of epididymo-cutaneous fistula in a person with cervical spinal cord injury ☆ , ☆ ☆," *Radiol. Case Reports*, vol. 17, no. 10, pp. 3938–3945, 2022, doi: 10.1016/j.radcr.2022.07.075.
- [21] L. Yijing *et al.*, "Impact of temperature condition in crop disease analyzing using machine learning algorithm," *BUILD. Environ.*, vol. 184, no. August, p. 107229, 2020, doi: 10.1016/j.buildenv.2021.06.011.
- [22] S. Suyanto, P. E. Yunanto, T. Wahyuningrum, and S. Khomsah, "A multi-voter multi-commission nearest neighbor classifier," *J. King Saud Univ. - Comput. Inf. Sci.*, no. xxxx, 2022, doi: 10.1016/j.jksuci.2022.01.018.
- [23] M. Cubillos, S. Wöhlk, and J. N. Wulff, "A bi-objective k -nearest-neighbors-based imputation method for multilevel data," *Expert Syst. Appl.*, vol. 204, no. February, p. 117298, 2022, doi: 10.1016/j.eswa.2022.117298.
- [24] X. Sun *et al.*, "Environmental Technology & Innovation Modeling and optimization of vegetable oil biodiesel production with heterogeneous nano catalytic process: Multi-layer perceptron, decision regression tree, and K-Nearest Neighbor methods," *Environ. Technol. Innov.*, vol. 27, p. 102794, 2022, doi: 10.1016/j.eti.2022.102794.
- [25] D. A. Adeniyi, Z. Wei, and Y. Yongquan, "Automated web usage data mining and recommendation system using K-Nearest Neighbor (KNN) classification method," *Appl. Comput. Informatics*, vol. 12, no. 1, pp. 90–108, 2016, doi: 10.1016/j.aci.2014.10.001.
- [26] Ş. Öztürk and B. Akdemir, "Application of Feature Extraction and Classification Methods for Histopathological Image using GLCM, LBP, LBGLCM, GLRLM and SFTA," *Procedia Comput. Sci.*, vol. 132, no. Iccids, pp. 40–46, 2018, doi: 10.1016/j.procs.2018.05.057.
- [27] M. J. Drielsma, J. Love, S. Taylor, R. Thapa, and K. J. Williams, "General Landscape Connectivity Model (GLCM): a new way to map whole of landscape biodiversity functional connectivity for operational planning and reporting," *Ecol. Modell.*, vol. 465, p. 109858, 2022, doi: 10.1016/j.ecolmodel.2021.109858.
- [28] S. Bakheet and A. Al-Hamadi, "Automatic detection of COVID-19 using pruned GLCM-Based texture features and LDCRF classification," *Comput. Biol. Med.*, vol. 137, no. June, p. 104781, 2021, doi: 10.1016/j.compbiomed.2021.104781.
- [29] A. Ansari, M. Heras, J. Nones, M. Mohammadpoor, and F. Torabi, "Predicting the performance of steam assisted gravity drainage (SAGD) method utilizing artificial neural network (ANN)," *Petroleum*, vol. 6, no. 4, pp. 368–374, 2020, doi: 10.1016/j.petlm.2019.04.001.
- [30] R. Shamass *et al.*, "Thin-Walled Structures Web-post buckling prediction resistance of steel beams with elliptically-based web openings using Artificial Neural Networks (ANN)," *Thin-Walled Struct.*, vol. 180, no. August, p. 109959, 2022, doi: 10.1016/j.tws.2022.109959.
- [31] A. Afandi, N. Lusi, I. Cutrawedarma, and B. Rudiyanto, "Prediction of Temperature in 2 Meters Temperature Probe Survey in Blawan Geothermal Field Using Artificial Neural Network (ANN) Method," *SSRN Electron. J.*, vol. 38, no. July, p. 102309, 2021, doi: 10.2139/ssrn.3954816.
- [32] R. Langbauer, G. Nunner, T. Zneck, J. Klarner, R. Prieler, and C. Hochenauer, "Development of an artificial neural network (ANN) model to predict the temperature of hot-rolled steel pipes," *Adv. Ind. Manuf. Eng.*, vol. 5, no. June, p. 100090, 2022, doi: 10.1016/j.aime.2022.100090.

5. Sertifikat



BINA INSANI UNIVERSITY

in cooperation with



APTIKOM

ANNALI PENGHIMPUN TUGAS INFORMASI DAN KOMPUTER



**ICCOSITE
2023**

The 2023 International Conference on
Computer Science, Information
Technology and Engineering
Jakarta - Indonesia



CERTIFICATE OF PRESENTER

No. 87/BIIIC/LPPM-BiU/II/2023

This is to certify that

Mardison Mardison and Yuhandri Yunus
(Universitas Putra Indonesia YPTK Padang, Indonesia)

has written the paper titled

Detection of Kidney Cysts of Kidney Ultrasound Image using Hybrid Method: KNN, GLCM, and ANN Backpropagation

at The 2023 International Conference on Computer Science, Information Technology and Engineering
with theme "Digital Transformation Strategy in Facing the VUCA and TUNA Era"
on 16 February 2023 in Jakarta, Indonesia

Rector of Bina Insani University



BINA INSANI UNIVERSITY

Assoc. Prof. Dr. Indra Muis, S.S.,M.M.

General Chair ICCOSITE 2023



BINA INSANI INTERNATIONAL CONFERENCE

Ahmad Chusyairi, M.Kom.

Sponsor:



IEEE
INDONESIA SECTION

Co-Host:



unindra
universitas indraprasta PGRI



UNIVERSITAS NASIONAL
PILIH PILIH PILIH



ITG

